

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
31 July 2003 (31.07.2003)


PCT

(10) International Publication Number
WO 03/062482 A2

- (51) International Patent Classification?: C22C 32/00
- (21) International Application Number: PCT/US03/01823
- (22) International Filing Date: 21 January 2003 (21.01.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/351,146 23 January 2002 (23.01.2002) US
- (71) Applicant (for all designated States except US): H. C. STARCK INC. [US/US]; 45 Industrial Place, Newton, MA 02161-1951 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): AIMONE, Paul, R. [US/US]; 20 Tanglewood Drive, Bridgewater, MA 02324-2275 (US); GOLDBERG, Howard, V. [US/US]; 34 Donna Road, Framingham, MA 017-7910 (US).
- MALEN, Richard [US/US]; 1 East Main Street, Ayer, MA 01432-1605 (US); MORSE, Thomas, A. [US/US]; 71 Spear Street, Melrose, MA 02176-5615 (US); KUMAR, Prabhat [US/US]; 31 Pinewood Avenue, Framingham, MA 01701-7656 (US); ULENHUT, Henning [US/US]; 566 Franklin St., Apt. 3, Cambridge, MA 02319 (US).
- (74) Agent: VAN EYL, Diderico; Bayer Corporation, 100 Bayer Road, Pittsburgh, PA 15205-9741 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: STABILIZED GRAIN SIZE REFRACTORY METAL POWDER METALLURGY MILL PRODUCTS



(57) Abstract: A powder metal (P/M) mill product and the method of fabrication such product made out of low oxygen (<400 ppm) refractory metal, or alloys thereof, using oxide additive (such as MgO, SiO₂, and Y₂O₃) for co-fabrication to achieve refractory metal grain size stabilization as required in high temperature applications. One such product is a sheet with small grain size containing oxide particles as grain size stabilizers. The product has good mechanical properties, low oxygen content in refractory metal fiber derivatives of the powder within the mill product and if is available as large pieces of sheet (lateral dimensions). The metal powder is consolidated to a sheet bar by different methods, which may weigh 50 pounds or more.